



- Protect-A-Pak is one of the world’s most popular single-use, low-cost impact indicators.
- Provides a visual indication that hidden damage may have occurred.
- When used with alert labels, a Protect-A-Pak reduces the incidence of damage by raising awareness that the package is being monitored.
- Promotes accountability amongst handlers throughout the transportation chain.
- Omnidirectional device, detects impacts from all directions.
- Can be mounted to a surface via self-adhesive or flush mounted with a mounting flange.
- Helps confirm the effectiveness of packaging
- Can help identify trouble spots in the transportation chain
- The cross spring and bearing design is engineered for simplicity and responsiveness.



Protect-A-Pak Companion Warning Label



Protect-A-Pak Flange Mount



Protect-A-Pak Specifications

Sensitivity:	10g-100g in 10g increments Also available in: 5g, 15g, 25g, 150g, 200g, 250g, 300g, and 500g.
Impact Duration:	9.6 ms
Height:	1" (2.5 cm)
Diameter:	1 1/4" (3.2 cm)
Weight:	1 oz. (28.35)
Operating Temperature:	-100°F to 155°F (-73°C to 68°C)
Accuracy:	±15%
Mounting:	Surface mounted via self-adhesive flush mounted via mounting flange.
Part Number:	1200-005G through 1200-500G

Impact-O-Graph Devices has a complete line of products for your transportation monitoring needs.

Visit us at: www.impactograph.com

Easy Installation

1. Remove manufacturing plug.
2. Twist the Mounting Flange into the box and put a Protect-A-Pak inside the flange and adhere a warning label on top to make flush or adhere by itself directly onto product box inside the

Date: 5/3/17